

BRIDGESTONE

VLT

V-STEEL  
L-TRACTION

E-3/L-3



V-Steel L-Traction (VLT) radial tire offers outstanding traction and flotation. The non-directional widebase design is ideal for scrapers, articulated dump trucks, and wheel loaders. Solid performance and maneuverability on wet, soft or muddy surfaces.



LOADERG



SCRAPERG



ARTICULATED DUMP TRUCKG

## SPECIALIZED FEATURES

### 1 INNOVATIVE TREAD LUGS DESIGN (COMPRESS AND EXPAND)

Provides powerful traction and self-cleaning capability

### 2 NON-DIRECTIONAL TREAD PATTERN

For self-cleaning in muddy surfaces

### 3 LARGE CONTACT FOOTPRINT

Provides excellent traction, flotation and rider comfort



BRIDGESTONE COMMERCIAL

See your Bridgestone representative for more information.



BS125 - V24 ©Bridgestone Americas Tire Operations LLC. All Rights Reserved.

BRIDGESTONE

Firestone

FEATURES & BENEFITS

**Innovative Tread Lugs provide great traction and self-cleaning properties.** As the tire moves, tread lugs compress and expand to provide powerful traction when needed and then eject mud to keep the tire clean and maintain good traction



**Innovative tread grooves and Ideal Lug Angle** provide excellent traction .

CATEGORY	SIZE	PLY/STAR RATING	COMPOUND/ CONSTRUCTION	TRA	ARTICLE #	AVG. WT. <sup>□</sup> [LBS / KG]	OTD <sup>□</sup> [32" / MM]	OVERALL DIAMETER <sup>□</sup> [IN / MM]	OVERALL WIDTH <sup>□</sup> [IN / MM]
SMALL TUBELESS	20.5R25	MS	DE2	E-3/L-3	421952	540 245	50 40	59.0 1,499	20.9 531
	23.5R25	MS	DE2	E-3/L-3	421960	799 363	54 43	63.9 1,623	24.3 617
	750/65R25	MS	DE2	E-3/L-3	420220	1,024 465	54 43	64.0 1,626	30.1 765
	26.5R25	MS	DE2	E-3/L-3	421979	1,040 472	57 45	68.8 1,748	26.9 583
	29.5R25	MS	DE2	E-3/L-3	421987	1,303 591	60 48	73.9 1,877	30.0 762
LARGE TUBELESS	33.25R29	2*	E2A	E-3	427645	1,830 831	68 54	81.9 2,075	33.6 864
	37.25R35	2*	E1A	E-3	427985	2,530 1,148	75 60	94.0 2,388	37.6 955
	37.25R35	2*	E2A	E-3	428002	2,654 1,205	75 60	94.0 2,388	37.6 955
	40.5/75R39	2*	E1A	E-3	428172	3,340 1,516	74 59	102.6 2,606	39.4 1,001
	40.5/75R39	2*	E2A	E-3	428138	3,581 1,626	74 59	102.6 2,606	39.4 1,001

<sup>□</sup> Actual specifications may vary depending on the tire produced. Off-road tire limited warranty information is available from your Bridgestone representative or dealer.