




The Smooth Tread-MS (STMS) bias tire is specially designed for severe rocky surfaces, such as underground mines, open pits, quarry and some port applications.

At Ports is used for reach stacker, top picks, and other container handling equipment, especially on abrasive concrete surfaces.



LOADERS

LHDs

CONTAINER HANDLERS (EMPTY)

STRADDLE CARRIERS

SPECIALIZED FEATURES

1 SMOOTH EXTRA DEEP TREAD PATTERN

For extended tire life and exceptional cut resistance and impact protection

2 EXTRA-DEEP & SPECIALLY COMPOUNDED RUBBER

Provides maximum resistance to wearing, heat and cutting

3 ALSO USED FOR CONTAINER HANDLER AND /OR PORT APPLICATIONS

Provides best riding comfort especially on abrasive concrete surfaces







CATEGORY	SIZE	PLY/STAR RATING	COMPOUND/ CONSTRUCTION	TRA	ARTICLE #	AVG. WT."	OTD ⁿ [32"]	OVERALL DIAMETER [IN]	OVERALL WIDTH [®]
SMALL TUBE TYPE	12.00-24	20	D2A	L-5S	295256	350	69	50.2	12.6
	14.00-24	20	D2A	L-5S	263303	534	98	54.1	14.4
SMALL TUBELESS	17.5-25	20	D2A	L-5S	261289	627	87	54.5	17.7
	18.00-25	32	D2A	L-5S	420972	1,092	106	65.9	20.5
	18.00-25	40	IDU	Industrial Service	422231	1,083	106	65.9	20.5
	26.5-25	32	D2A	L-5S	275573	1,869	120	70.8	26.8
	26.5-25	36	D2A	L-5S	421863	1,904	120	70.8	26.8
LARGE TUBELESS	29.5-29	34	D2A	L-5S	419095	2,384	130	79.6	29.5
	35/65-33	42	D2V	L-5S	424874	3,298	122	81.7	35.3
	45/65-45	58	D2V	L-5S	422657	6,681	146	107.5	45.1

Actual specifications may vary depending on the tire produced. Off-road tire limited warranty information is available from your Bridgestone representative or dealer.

